

System Capacity

		KX-TDA15	KX-TDA30	KX-TDA30 with Memory Expansion card (KX-TDA3105)
Extensions	Max Extension Port (DPT and SLT)	20	28	52
	Single Line (a/b) Telephone (SLT)	12	24	24
	Digital Proprietary Telephone (DPT) Note 1 (Type 1)	16	24	48
	Digital Proprietary Telephone (DPT) Note 2 (Type 2)	4	24	24
	IP Proprietary Telephone (IPT) Note 3	4	4	4
	Analogue Proprietary Telephone (APT)	4	4	4
	Direct Station Select (DSS) Console	4	4	4
	Voice Processing System (VPS)	1 (4 ports)	1 (4 ports)	1 (4 ports)
Trunks	Trunk Port	8	12	12
	ISDN Trunk (BRI)	4	6	6
	Analogue Trunk	2	12	12
	IP-Trunk	4	4	4
	SIP Trunk (including TDA3451)	4 (8)	4 (8)	4 (8)
Wireless	Portable Station (PS)	28	28	28
	Cell Station (CS)	4	8	8
Doorphone Port		4	4	4

Note 1: (Type 1): T7600 series, T7560, T7565 Digital Proprietary Telephones

Note 2: (Type 2): Current Digital Proprietary Telephones (T7200, T7400, T7500 series)

Note 3: NT136, NT265, and NT300 series IP Proprietary Telephones



Line-up
KX-TDA15 and KX-TDA30

Option List for TDA15/30

	Model	Description	Maximum Quantity	
			KX-TDA15	KX-TDA30
Main Board	Daughter cards for KX-TDA30 Main Board	Memory Expansion Card (MEC)	n/a	1
		Remote Card (RMT)	n/a	1
Option Cards	KX-TDA3180	4-Port Analogue Trunk Card (LCOT4)	n/a	3
	Daughter card for KX-TDA3180	4-Port Caller ID Card (CID4)	n/a	3
	KX-TDA3183	2-Port Analogue Trunk Card (LCOT2)	1	3
	KX-TDA3280	2-Port BRI Card (BRI2)	1	3
	KX-TDA3283	1-Port BRI Card (BRI1)	1	n/a
	KX-TDA3450	4-Channel SIP Trunk Card (SIP-GW4)	1	1
	Daughter card for KX-TDA3450	4-Channel VoIP DSP Card (SIP-DSP4)	1	1
	KX-TDA3480	4-Channel VoIP Gateway Card (IP-GW4)	1	1
	KX-TDA3171	4-Port Digital Extension Card (DLC4)	n/a	1
	KX-TDA3172	8-Port Digital Extension Card (DLC8)	1	2
Extension Cards	KX-TDA3173	4-Port Single Line Telephone Extension Card (SLC4)	n/a	1
	KX-TDA3174	8-Port Single Line Telephone Extension Card (SLC8)	1	2
	KX-TDA3470	4-Channel VoIP Extension Card (IP-EXT4)	1	1
	KX-TDA3161	4-Port Doorphone and External Input / Output Card (DPH4)	1	1
	KX-TDA3162	2-Port Doorphone and External Input / Output Card (for German Type)	1	1
	KX-TDA3166	8-Channel Echo Canceller Card (ECHO8)	1	1
	KX-TDA3168	Extension Caller ID Card (EXT-CID)	Preinstalled	1
DECT Options	KX-TDA3191	2-Channel Message Card (MSG2)*1	2	2
	KX-TDA3192	2-Channel Simple Voice Message Card (SVM2)	2	2
	KX-TDA0141CE	2-Channel Cell Station for DHL / DLC Card	4	8
	KX-TDA0158	8-Channel High Density Cell Station for DHL / DLC Card	2	4
Additional Accessories	KX-A272	2-Channel DECT Cell Station Repeater	6 per base	6 per base
	KX-TDA3820	SD Card - Standard feature Upgrades	1	1
	KX-TDA3920	SD Card - Enhanced feature Upgrades	1	1
	KX-A244	19" Rack Mounting Bracket	1	1
	KX-A236	Additional AC Adaptor and AC Cord	n/a	1
	KX-A228	Battery Back-Up Cable	n/a	1
	KX-T7765	Doorphone	4	4
	KX-A289	KX-TCA256 Transparent Front Carry Case	-	-
	KX-A287	KX-TCA256 Belt Clip Carry Case	-	-
	KX-A288	KX-TCA155 Transparent Front Carry Case	-	-
KX-A290	KX-TCA355 Belt Clip Carry Case	-	-	
CTI Applications	KX-TDA0350	PC Phone - 1st Party CTI Software / PC Phone Software Add-in for Microsoft® Outlook®	16 / 16	48 / 48
	KX-TDA0300	PC Console - Operator Software with system directory capabilities	12	24
	KX-NC51100*2	Phone Assistant Pro Trial / Express	7	7
	KX-NC51101	Phone Assistant Pro - 1 licence	30*3	30*3
	KX-NC51105	Phone Assistant Pro - 5 licences		
	KX-NC51110	Phone Assistant Pro - 10 licences		
	KX-NC51199	Phone Assistant Pro - 128 licences		
	KX-NC51200*2	Phone Assistant Status Pro Trial / Express	3	3
	KX-NC51201	Phone Assistant Status Pro (1 licence)	8	8
	KX-NC51301*2	Phone Assistant Manager	16	16
	KX-NC58100/8101	IP Softphone	4	4
	KX-NC59101	IP Softphone Plug-in (KX-NC51101,1105,1110,1199)	4	4

*1 Total Record time: 8 minutes per system. Up to 32 messages, maximum 1 minute per message.

*2 Software bundled free with TDA30 PBX (Not TDA15)

*3 Limited by Maximum Extension capacity

Specifications

KX-TDA15/30
Power Voltage: AC100V ~ 240V 50 / 60 Hz
Memory Back-up Duration: 7 years
Dialling: Extension - DP (10pps, 20pps), DTMF CO - DP (10pps, 20pps), DTMF
Mode Conversion: DP-DTMF, DTMF-DP
Connectors: CO Line - RJ45 (2 wire) x each Trunk port Station - RJ45 (4 wire) x each Extension port Paging Output - 1 conductor jack External MOH Output - 1 conductor jack
Ring Frequency: 20/25 Hz (Selectable)
Trunk Loop Limit: 1600 ohms Max.
Operating Environment: Humidity - 10 - 90% (non condensing)
MOH (Music On Hold): 1 port (Level Control: -11dB to +11dB in 1dB steps) Selectable Tone/External Music Source Port
Internal Paging Volume: Level control: -15dB to +6dB per 3dB
External Paging: 1 port (Level control: -15dB to +15dB per 3dB)
Serial Interface Port: USB: 1 port RS-232C: 1 port (115.2kbps)
Structure: Free Slot style Can be accommodated into 19" Rack
Dimensions: 275mm (W) x 376mm (H) x 117mm (D)
Weight: Under 3.5Kg

System Feature Capacity

		KX-TDA15/30	
System	Tenant	8	
	Class of Service	64	
	Trunk Group	64	
	User Group	32	
	Paging Group	32	
	Call Pickup Group	64	
	Incoming Call Distribution (ICD) Group	128 (32 extensions per group)	
	Portable station (PS) Ring Group	32	
	Voice Mail (DPT) Group	1 group * 4 ports	
	Voice Mail (DTMF) Group	2 groups x 24 ch	
	Queuing Time Table	64	
	Idle Extension Hunting Group	64 (16 extensions / table)	
	Absent Message (System / Extension)	8 message x 16 characters per system 1 message x 16 characters per extension	
	Message Waiting	256	
	Number of the characters of Name	20	
	Extension Number Digits	1 - 4 digits	
	Call Park Zone	100	
	Conference	3-8 parties per conference	
	Special Carrier Code	16 digits, 20 entries	
	Verification Code	4 digits x 1000 entries	
	Verification Code Personal Identification Number (PIN)	10 digits, 1000 entries	
	Host PBX Access Code	10 digits, (10 entries / trunk group)	
	DDI/DID Table	32 digits (1000 entries)	
	Station Message Detailed Recording (SMDR) Call Storage	200 calls	
	Toll Restriction / Barring	Toll Restriction/Barring Level	7
		Toll Restriction /Barring Denied Code	16 digits, 100 entries per level
		Toll Restriction /Barring Exception Code	16 digits, 100 entries per level
Call Log	Outgoing Call Log	100 logs per extension	
	Incoming Call Log	1000 logs per extension	

		KX-TDA15/30
Networking	TIE Routing Table	32 entries
	Leading Number	3 digits
	PBX Code	7 digits
	NDSS: Monitored PBX	8
	NDSS: Registered Extension, Monitoring on PBX	250
Automatic Route Selection (ARS)	Routing Plan Table	16 entries
	Leading Number Table	16 digits, 1000 entries
	Leading Number Exception Table	16 digits, 200 entries
	ARS Carrier	10
	Itemised Billing Code	10 digits
	Authorisation Code	10 digits
Dialling	Emergency Call	32 digits, 10 entries
	Quick Dialling	4 digits, 80 entries
	System Speed Dialling	32 digits, 1000 entries per system w/o EMEC card 32 digits, 1000 entries per Tenant w EMEC card Max: 8 Tenants
	Personal Speed Dialling	32 digits, 10 entries per extension w/o EMEC 32 digits, 100 entries per extension w EMEC
	One-Touch Dialling	32 digits
	Hot Line	32 digits
	Key Pad Protocol Dial (ISDN Service Access)	32 digits
Password	Redial	32 digits
	System Password for Administrator -for PT	4-10 digits
	System Password for User	4-10 digits
	Manager Password	4-10 digits
	Extension Personal Identification Number (PIN)	0-10 digits / extension
Voice Mail	Max Number of VPS Systems	1
	Max Number of VPS Channels	1 x 8 ch
Voice Message SVM	Outgoing Message (OGM)	32
	OGM Total Recording Time	8 minutes
	Voice Messages	125 messages/card
	SVM Total Recording Time	40, 60 or 120 minutes (depending on recording quality)

Feature List

System Features

- Automatic Call Distribution (ARS)
- Automatic ISDN Setting (BRI)
- Automatic Route Selection (ARS) / Least Cost Routing (LCR)
- Background Music (BGM)
- Budget Management
- Busy on Busy
- Call Park with Indication
- Call Pickup Group
- Call Distribution by Caller ID
- Class of Service (COS)
- CTI (CSTA, TAPI)
- Data Line Security
- Delayed Ringing
- Direct In Lines (DIL)
- Direct Dial In (DDI)
- Direct Inward System Access (DISA)
- Door-Phone / Door Opener
- Echo Cancellation
- Extension Lock
- External Sensor/Relay for Alarm Notification
- Emergency Call
- Existing APT / DPT Compatibility
- External BGM
- Flexible Numbering Plan
- Floating Extension
- Greeting Message
- Host PBX Access Code
- Hunting Group
- Hurry-Up Transfer
- Incoming Call Distribution (ICD) group - Hunting Group
- Incoming Call Group (ICD) Call Log
- Intercept Routing - Busy / DND
- Intercept Routing - Busy (Default destination)
- Intercept Routing - DISA Message
- Intercept Routing - No Answer *4
- Intercept Routing - Time Service (Day/Night/Lunch/Break)
- Intercept to Extension
- Intercept to Trunk
- Line Monitor (CO)
- Main Processing Card (MPR) / CS Software Download
- Manager Functions
- Multiple Language Support
- Online Diagnostics
- Operator Functions
- PC Console / PC Phone
- PC Programming
- Paging Group
- Primary Directory Numbers (PDN)
- Secondary Directory Numbers (SDN)
- Remote Extension Status Control through DISA
- Remote Extension Lock
- Ring Group
- Special Carrier Access
- Station Message Detail Recording (SMDR)
- SMDR 12 and 24 Hour Time Format
- SMDR Caller ID Printing
- System Memory Expansion*3

- Tenant Service
- Timed Reminder
- Time Service (Day/Night/Lunch/Break)
- Toll Restriction
- Trunk Group
- Uniform Call Distribution (UCD)
- User Group
- VIP-Call
- Visual Caller ID

<Voice Mail (VM) Features>

- Automatic Configuration - Quick Setup
- Call Forwarding to VM
- Caller's Identification Notification to VM
- DISA and Auto Attendant (SVM)
- Email Integration*2
- Intercept Routing to VM
- LCD for VM operation (KX-T7636/33 only)
- Live Call Screening (LCS)
- Remote PBX Data Control by VM
- VM clear via CTI
- VM Data Control by PBX
- VM (Digital / DTMF) Integration
- VM Group
- VM Mail Transfer with Caller ID
- VM Message Number display on DPT LCD

Extension Features

- 4-Party Conference with Broadcasting up to 32-Party
- Absent Message
- Account Code Entry (Forced)
- Automatic Answer from transfer
- Automatic Call Waiting
- Automatic Redial
- Boss - Secretary
- Broadcasting
- Caller ID to SLT
- Call Forwarding (All Calls, Busy, Busy/No Answer, No Answer, Follow Me, From Incoming Group)
- Call Hold
- Call Pick-up (Directed, Group, DSS, Deny)
- Call Transfer (Screened, Unscreened, One-Touch Transfer, Transfer Recall)
- Conference (3-Party Conference, Multi Party conference, Unattended Conference)
- Dial Type Selection
- Digital Duplex Speaker Phone (SP-phone)
- Digital eXtra Device Port (DXDP)
- Direct One-Touch Answering
- Do Not Disturb (DND)
- DSS Console
- Executive Busy Override
- Extension Directory
- Extension-to-Trunk Call duration Time
- External Feature Access
- Flexible Buttons
- Hands-free Operation
- Handset / Headset Selection
- Large Telephone Display Features with Back-light
- LED control for CTI

- Log-In / Log-Out
- Message Waiting
- Multi-Lingual Display
- Multiple Hop Call Forwarding (4 steps)
- Music on Hold by DDI/DIL Tenant
- Off-Hook Call Announcement (OHCA)
- Off-Hook Monitor
- One-Touch Dialling
- Paging (Deny, Paging Transfer)
- Paralleled Telephone (APT/DPT & SLT, DPT/SLT & PS, DPT/SLT & Mobile Telephone)
- Quick Dial
- Redial, Last Number
- Remote Station Control
- Special Carrier Access
- Speed Dialling - Personal & System
- Time and Date Display
- Tone Pulse Conversion
- Trunk Answer from Any Station (TAFAS)
- Walking Class Of Service (COS) multiple CLIP
- Whisper OHCA (Off-Hook Call Announcement)
- Wrap-Up
- eXtra Device Port (XDP)

DECT Features

- Automatic Handover
- DECT CS on Digital Extension Port
- Headset Compatibility
- Incoming & Outgoing Call Log
- LCD Control via CTI*1
- Wireless XDP Parallel Mode (SXDP)
- Vibrator Ring (KX-TCA256/355 Only)

ISDN Service Features

- Advice of Charge (AOC)
- Alert Connect mode
- Call Hold (HOLD)
- Calling Line Identification Restriction (CLIR)
- Calling Line Identification Presentation (CLIP)
- Completion of Calls to Busy Subscriber (CCBS)
- Connected Line Identification Presentation (COLP)
- Connected Line Identification Restriction (COLR)
- Direct Dialling Inward (DDI)
- ISDN 3 Party Conference (3PTY)
- ISDN Call Forwarding (CFU / CFNR / CFB)
- ISDN Call Transfer (CT)
- ISDN Extension
- Malicious Call Identification (MCID)
- Multiple Subscriber Numbers (MSN)

Built-in Hotel Features

- Call Billing for Guest Room
- Check-in / Check-out
- Remote Wake-up Call
- Room Status Control
- SMDR for External Hotel Application

Mobile Telephone Integration Features

- Call Transfer*1
- Incoming Call Distribution (ICD) group*1
- System Feature Access*1

Networking Features

- Alternate Routing
- ARS with VoIP
- Centralised Voice Mail*1
- Common Extension Numbering*1
- DECT PS roaming using Network ICD*1
- DISA Call to the Network
- Network Busy Lamp Field (BLF)*1
- Network Closed Numbering
- Network Incoming Call Distribution (ICD) group*1
- Private Network to Public Network
- Public Network to Private Network
- QSIG Connection
- QSIG Access to CO line
- Tandem Connection
- TIE Line
- Transfer to Network PBX
- Virtual Private Network (VPN)
- VoIP Network

IP Telephone Features

- KX-NT300 series support*5

*1 TDA3920 Optional software required

*2 When integrated with a KX-TVM50/200 Voice Processing system.

*3 KX-TDA30 only

*4 Day/Lunch/Break/Night/Busy

*5 Requires IP Extension Card

DPT: Digital Proprietary Telephone
APT: Analogue Proprietary Telephone
SLT: Single Line Telephone
IPT: IP Proprietary Telephone
PS: Portable Station